

## HPL SOLID GRADE LAMINATE

**For cubicle systems Cronus NR, type F, Basic type C  
Locker systems and doors, type P, type R, and type S  
Vanity units type W HPL and type W Bambino  
Doors type T  
Bench seating type U**

Made by KEMMLIT-Bauelemente GmbH  
Maltschachstr. 37  
Germany  
72144 Dusslingen  
Telephone: 0049 (0) 7072 / 131-0  
Telefax: 0049 (0) 7072 / 131-150  
info@kemmlit.de - www.kemmlit.de

HPL solid grade laminate panels are usually easy to clean. Please do not use any aggressive cleaning agents. If special cleaning agents need to be used to remove stubborn stains, please make sure to adhere to the appropriate accident prevention and precaution instructions of the cleaning product. Please make sure to ventilate the rooms sufficiently.

### **I. REGULAR CLEANING:**

For everyday cleaning of regular stains please use clean hot water, clean cloth, a soft sponge or a soft nylon brush, all purpose cleaning agents without any abrasive elements, as well as washing powder, soft soap or curd soap. After cleaning please remove cleaning agents completely to prevent smears. Wipe the surface dry with an absorbent clean cloth. Please change the cloth frequently.

### **II. HEAVY STAINING:**

Please remove dark, stubborn stains such as grease, oil, felt pen, lipstick, water soluble colours, nicotine, urine etc. with hot water and all purpose cleaner (e.g. powder cleaner). Depending on the degree of staining please let the foam effect the stains before rinsing with clean water. Then, please dry the surface with an absorbent, clean cloth. The following cleaning agents must not be used:

Grinding and scrubbing agents (abrasives, steel wool), polishing agents, wax, bleaching agents, cleaning agents containing strong acids, e.g. decalcifier with formic acid and amino-sulpho-acid, drain pipe cleaner, hydrochloric cleaner and cleaning agents for silverware.

### **III. ATTENTION:**

Lime residue can be removed with acidic cleaning agents, containing approximately 10 % citric or acetic acid. Please adhere to the special instructions marked on the cleaning agents. After cleaning surfaces must be washed off with clean water. Please remove solvable paints, lacquers, ink, shoe polish with organic cleaning agents (acetone, spirit, turpentine, benzine). Please rub off silicone with dry cloth or use silicone remover

### **IV. CLEANING WITH HIGH-PRESSURE CLEANER**

HPL solid grade laminate panels are resistant to common desinfectant such as

- Alcohol (60 – 70 % solution with water)
  - Aldehyde, but not in conjunction with quaternary ammonium compound
  - Chlorine-releasing compounds (if used regularly it can result in a paling of the colour pigments)
  - Phenol (not allowed for cleaning of kitchens)
  - Peroxyde compound (especially hydrogen peroxide and organic acids)
  - Quaternary ammonium compound
- Detergent-sanitisers are to be used for the cleaning and disinfection of moderately stained surfaces in areas with a great danger of infection.